



DECLARATION OF PERFORMANCE

No. KAQ_0428

1. Unique identification code of the product-type: **AQUAPANEL® SkyLite Joint Filler & Skim Coating SLJFSC_475694_012**
2. Intended use/es: **Cement-bound filling material for joint filling and skim coating by hand and machine of AQUAPANEL® Cement Board SkyLite**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**
Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: aquapanel.info@knauf.com
4. Authorised representative: not applicable
5. System/s of AVCP: **System 4**
6. a) Harmonised standard: **EN 998-1:2010-10**
Notified body/ies: not applicable
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body /
Notified body/ies: not applicable
7. Declared performance/s:

Essential characteristics	Performance	Harmonised tech. specification
Mortar class	Lightweight plastering mortar (LW) for internal and external use (CS II)	EN 998-1:2010-10
Reaction to fire	A1	EN 998-1:2010-10
Water absorption	W1	EN 998-1:2010-10
Water vapour diffusion coefficient	$\mu = 5$ (wet cup); $\mu = 20$ (dry cup) table value according to EN 1745	EN 998-1:2010-10
Adhesion	$\geq 0,20$ N/mm ² , FP: B	EN 998-1:2010-10
Thermal conductivity ($\lambda_{10,dry}$)	$\leq 0,16$ W/mK for P = 50%; $\leq 0,17$ W/mK for P = 90% (Table value according to EN 1745)	EN 998-1:2010-10
Durability	NPD	EN 998-1:2010-10

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski, General Manager

Iserlohn, 10.06.2016

28.5.2014 L 159/43 Official Journal of the European Union EN

AQUAPANEL®

Be certain, choose AQUAPANEL®