



DECLARATION OF PERFORMANCE

No. KAQ_0429

1. Unique identification code of the product-type: **AQUAPANEL® Rustproofed Screw SN 40 SN40_87197_017**
2. Intended use/es: **Mechanical fasteners for wooden constructions**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**
Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: aquapanel.info@knauf.com
4. Authorised representative: not applicable
5. System/s of AVCP: **System 3**
6. a) Harmonised standard: **EN 14592:2008+A1:2012**
Notified body/ies: **SZU BRNO (1015)**
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body /
Notified body/ies: not applicable
7. Declared performance/s:

Essential characteristics	Performance	Harmonised tech. specification
Characteristic yield moment $M_{y,k}$	2.911 Nmm	EN 14592:2008+A1:2012
Characteristic withdrawal parameter $f_{ax,k}$	18,39 / 12,07 N/mm ² loading across the fibre / along the fibre Wood density: 360 kg/m ³	EN 14592:2008+A1:2012
Characteristic head pull-through parameter $f_{head,k}$	26,54 N/mm ² Wood density: 360 kg/m ³	EN 14592:2008+A1:2012
Characteristic tensile capacity $f_{tens,k}$	4,68 kN	EN 14592:2008+A1:2012
Characteristic torsional ratio $f_{tor,k}$	2,45 Nmm Wood density: 450 kg/m ³	EN 14592:2008+A1:2012
Durability (i.e. corrosion protection)	Stainless steel A2 (1.4567) (Service class 3 acc. to EN 1995-1-1)	EN 14592:2008+A1:2012

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski, General Manager

Iserlohn, 10.06.2016

28.5.2014 L 159/43 Official Journal of the European Union EN

Be certain, choose AQUAPANEL®