



AQUAPANEL®

08/2017

AQUAPANEL®
Rustproofed Screw SB 40
for AQUAPANEL® Cement Board Outdoor



Description

AQUAPANEL® Rustproofed Screw SB 40 has been specially developed for fixing AQUAPANEL® Cement Board Outdoor to aluminium substructures. The screw length is $l = 40$ mm.

The screws are made from V2A stainless steel. The AQUAPANEL® Rustproofed-Screw SB 40 has a HiLo-thread.

The screw also has milling ribs under the countersunk head, ensuring a flush and clean countersinking of the head.

The screws have a star drive for the optimized transmission of torques.

Processing

The screws are installed flush so that the screw heads are level with the plane of the board with screw spacing ≤ 250 mm. Note the spacing from the edges of minimum 15 mm. The use of screwdrivers with depth control is recommended.

Material coverage

Wall: 15 screws/m², stud spacing 60 cm
25 screws/m², stud spacing 30 cm
Ceiling: 25 screws/m², stud spacing 30 cm

Method of delivery

AQUAPANEL® Rustproofed Screw SB 40: 250 pcs/pack

Item code: 424110

AQUAPANEL®

www.AQUAPANEL.com

aquapanel.info@knauf.com

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany